

Football Equipment

5 9/16" Gooseneck Goalposts

FB55CG 5 9/16" Gooseneck College Goalposts

Applies also to FB55CG-SY and FB55CG-WT

Goalposts shall meet all NCAA rules. Goalposts shall be of the single bent post design and provide a minimum of 72" of setback from the front of the post to the front of the horizontal crossbar. The bent post shall be a minimum of 5" schedule 40 (5 9/16" outside diameter) ASTM A500 grade C structural pipe and provide for no less than 48" bury into the ground.

Horizontal crossbars shall be no less than 4-1/2" OD flow coated steel tubing with a 7 gauge wall thickness and be of a length to allow uprights to extend upward with official college 18'6" between the upright members. Two vertical uprights shall rise a minimum of 20' above the top of the crossbar. Uprights shall be constructed of 2 3/8" diameter 6063-T6 aluminum with a minimum 0.154" wall thickness. Uprights shall be connected to each end of the crossbar by means of a machined aluminum insert that allows the angle of the uprights to be adjusted at the time of field installation. The insert design shall allow rain to escape through the insert from the top of the uprights.

The crossbar shall be attached to the bent post by means of an adjustable "T" adapter that allows field adjustment of the horizontal crossbar for ease and accuracy of installation.

All steel and aluminum members shall have a polyester powder coated finish (white or safety yellow). All hardware shall be zinc plated grade 5 minimum. Optional features include ground sleeves, safety padding and wind direction flags. Shipping weight approximately 1075#/pair.

FB55HS 5 9/16" Gooseneck High School Goalposts

Applies also to FB55HS-SY and FB55HS-WT

Goalposts shall meet all National High School Federation rules. Goalposts shall be of the single bent post design and provide a minimum of 72" of setback from the front of the post to the front of the horizontal crossbar. The bent post shall be a minimum of 5" schedule 40 (5 9/16" outside diameter) ASTM A500 grade C structural pipe and provide for no less than 48" bury into the ground.

Horizontal crossbars shall be no less than 4-1/2" OD flow coated steel tubing with a 7 gauge wall thickness and be of a length to allow uprights to extend upward with official high school 23'4" between the upright members. Two vertical uprights shall rise a minimum of 20' above the top of the crossbar. Uprights shall be constructed of 2 3/8" diameter 6063-T6 aluminum with a minimum 0.154" wall thickness. Uprights shall be connected to each end of the crossbar by means of a machined aluminum insert that allows the angle of the uprights to be adjusted at the time of field installation. The insert design shall allow rain to escape through the insert from the top of the uprights.

The crossbar shall be attached to the bent post by means of an adjustable "T" adapter that allows field adjustment of the horizontal crossbar for ease and accuracy of installation.

All steel and aluminum members shall have a polyester powder coated finish (white or safety yellow). All hardware shall be zinc plated grade 5 minimum. Optional features include ground sleeves, safety padding and wind direction flags. Shipping weight approximately 1200#/pair.

**FB55HSCG 5 9/16" Combination High School/College Football Goal Posts
Applies also to FB55HSCG-SY and FB55HSCG-WT**

Goalposts shall meet all National High School Federation rules. Goalposts shall be of the single bent post design and provide a minimum of 72" of setback from the front of the post to the front of the horizontal crossbar. The bent post shall be a minimum of 5" schedule 40 (5 9/16" outside diameter) ASTM A500 grade C structural pipe and provide for no less than 48" bury into the ground.

Horizontal crossbars shall be no less than 4-1/2" OD flow coated steel tubing with a 7 gauge wall thickness. Crossbars shall extend from official 18'6" college length to official 23'4" high school width by means of a telescoping aluminum inner tube. Two vertical uprights shall rise a minimum of 20' above the top of the crossbar. Uprights shall be constructed of 2 3/8" diameter 6063-T6 aluminum with a minimum 0.154" wall thickness. Uprights shall be connected to each end of the crossbar by means of a machined aluminum insert that allows the angle of the uprights to be adjusted at the time of field installation. The insert design shall allow rain to escape through the insert from the top of the uprights.

The crossbar shall be attached to the bent post by means of an adjustable "T" adapter that allows field adjustment of the horizontal crossbar for ease and accuracy of installation.

All steel and aluminum members shall have a polyester powder coated finish (white or safety yellow). All hardware shall be zinc plated grade 5 minimum. Optional features include ground sleeves, safety padding and wind direction flags. Shipping weight approximately 1350#/pair.

FB58CG 5-9/16" Gooseneck College Goalposts

Applies also to FB58CG-SY and FB58CG-WT

Goalposts shall meet all NCAA rules. Goalposts shall be of the single bent post design and provide a minimum of 96" of setback from the front of the post to the front of the horizontal crossbar. The bent post shall be a minimum of 5" schedule 40 (5 9/16" outside diameter) ASTM A500 grade C structural pipe and provide for no less than 48" bury into the ground.

Horizontal crossbars shall be no less than 4-½" OD flow coated steel tubing with a 7 gauge wall thickness and be of a length to allow uprights to extend upward with official college 18'6" between the upright members. Two vertical uprights shall rise a minimum of 20' above the top of the crossbar. Uprights shall be constructed of 2 3/8" diameter 6063-T6 aluminum with a minimum 0.154" wall thickness. Uprights shall be connected to each end of the crossbar by means of a machined aluminum insert that allows the angle of the uprights to be adjusted at the time of field installation. The insert design shall allow rain to escape through the insert from the top of the uprights.

The crossbar shall be attached to the bent post by means of an adjustable "T" adapter that allows field adjustment of the horizontal crossbar for ease and accuracy of installation. All steel and aluminum members shall have a polyester powder coated finish (white or safety yellow). All hardware shall be zinc plated grade 5 minimum. Optional features include ground sleeves, safety padding and wind direction flags. Shipping weight approximately 1250#/pair.

FB58HS 5-9/16" Gooseneck High School Goalposts

Applies also to FB58HS-SY and FB58HS-WT

Goalposts shall meet all National High School Federation rules. Goalposts shall be of the single bent post design and provide a minimum of 96" of setback from the front of the post to the front of the horizontal crossbar. The bent post shall be a minimum of 5" schedule 40 (5 9/16" outside diameter) ASTM A500 grade C structural pipe and provide for no less than 48" bury into the ground.

Horizontal crossbars shall be no less than 4-1/2" OD flow coated steel tubing with a 7 gauge wall thickness and be of a length to allow uprights to extend upward with official high school 23'4" between the upright members. Two vertical uprights shall rise a minimum of 20' above the top of the crossbar. Uprights shall be constructed of 2 3/8" diameter 6063-T6 aluminum with a minimum 0.154" wall thickness. Uprights shall be connected to each end of the crossbar by means of a machined aluminum insert that allows the angle of the uprights to be adjusted at the time of field installation. The insert design shall allow rain to escape through the insert from the top of the uprights.

The crossbar shall be attached to the bent post by means of an adjustable "T" adapter that allows field adjustment of the horizontal crossbar for ease and accuracy of installation. All steel and aluminum members shall have a polyester powder coated finish (white or safety yellow). All hardware shall be zinc plated grade 5 minimum. Optional features include ground sleeves, safety padding and wind direction flags. Shipping weight approximately 1250#/pair.

**FB58HSCG 5 9/16" Combination High School/College Football Goal Posts
Applies also to FB58HSCG-SY and FB58HSCG-WT**

Goalposts shall meet all National High School Federation rules. Goalposts shall be of the single bent post design and provide a minimum of 96" of setback from the front of the post to the front of the horizontal crossbar. The bent post shall be a minimum of 5" schedule 40 (5 9/16" outside diameter) ASTM A500 grade C structural pipe and provide for no less than 48" bury into the ground.

Horizontal crossbars shall be no less than 4-1/2" OD flow coated steel tubing with a 7 gauge wall thickness. Crossbars shall extend from official 18'6" college length to official 23'4" high school width by means of a telescoping aluminum inner tube. Two vertical uprights shall rise a minimum of 20' above the top of the crossbar. Uprights shall be constructed of 2 3/8" diameter 6063-T6 aluminum with a minimum 0.154" wall thickness. Uprights shall be connected to each end of the crossbar by means of a machined aluminum insert that allows the angle of the uprights to be adjusted at the time of field installation. The insert design shall allow rain to escape through the insert from the top of the uprights.

The crossbar shall be attached to the bent post by means of an adjustable "T" adapter that allows field adjustment of the horizontal crossbar for ease and accuracy of installation.

All steel and aluminum members shall have a polyester powder coated finish (white or safety yellow). All hardware shall be zinc plated grade 5 minimum. Optional features include ground sleeves, safety padding and wind direction flags. Shipping weight approximately 1400#/pair.