

4" Square Portable Aluminum Soccer Goals

SC1865PA44E Club 4" x 4", 18 ½' x 6 ½' Aluminum Portable Goals

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum ¾" corner radii for safety and a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 18 ½' wide x 6 ½' high opening.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 6 ½' bottom depth.

4" square face of the goal shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty and comply with ASTM F2056.

Standard features shall include auger type rear safety hold downs, molded plastic net attachment clips, rear horizontal stabilizer bars, Velcro net straps and net ground stakes. System shall weigh approximately 345#/pair.

SC1865PA44NT No Tip™ Club 4" x 4", 18 ½' x 6 ½' Aluminum Portable Goals

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum ¾" corner radii for safety and a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 6 ½' bottom depth.

4" square face of the goal shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty and comply with ASTM F2056.

Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels.

Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. System shall weigh approximately 450#/pair.

SC2170PA44E Club Plus 4" x 4", 21' x 7' Aluminum Portable Goals

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum 3/4" corner radii for safety and a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 21' wide x 7' high opening.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 7' bottom depth.

4" square face of the goal shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty and comply with ASTM F2056.

Standard features shall include auger type rear safety hold downs, molded plastic net attachment clips, rear horizontal stabilizer bars, Velcro net straps and net ground stakes. System shall weigh approximately 388#/pair.

SC2170PA44NT No Tip™ Club Plus 4" x 4", 21' x 7' Aluminum Portable Goals

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum 3/4" corner radii for safety and a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 7' bottom depth.

4" square face of the goal shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty and comply with ASTM F2056.

Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels.

Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. System shall weigh approximately 490#/pair.

SC2480PA44E Competition 4" x 4", Official 24' x 8' Aluminum Portable Goals

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum $\frac{3}{4}$ " corner radii for safety and a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

Goal shall be designed so that it can be assembled with an official 24' wide x 8' high opening (or 24' 1 $\frac{1}{4}$ " or 24' 2" wide to compensate for the use of optional safety padding on the vertical posts without affecting the 24' goal width). The backstays and rear stabilizer bar shall be constructed of 1 $\frac{5}{8}$ " diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 10' bottom depth.

4" square face of the goal shall have a white textured polyester powder coated finish. Goal shall meet all NCAA, NF and FIFA rules and comply with ASTM F2056 and shall carry an 8-year limited warranty.

Standard features shall include auger type rear safety hold downs, molded plastic net attachment clips, rear horizontal stabilizer bars, Velcro net straps and net ground stakes. System shall weigh approximately 435#/pair.

SC2480PA44NT No Tip™ Competition 4" x 4", Official 24' x 8' Aluminum Portable Goals

Face of goal shall be constructed of 4" square extruded 6063-T6 aluminum with minimum $\frac{3}{4}$ " corner radii for safety and a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

Goal shall be designed so that it can be assembled with an official 24' wide x 8' high opening (or 24' 1 $\frac{1}{4}$ " or 24' 2" wide to compensate for the use of optional safety padding on the vertical posts without affecting the 24' goal width). The backstays and rear stabilizer bar shall be constructed of 1 $\frac{5}{8}$ " diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 10' bottom depth.

4" square face of the goal shall have a white textured polyester powder coated finish. Goal shall meet all NCAA, NF and FIFA rules and comply with ASTM F2056 and shall carry an 8-year limited warranty.

Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels.

Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. System shall weigh approximately 540#/pair.

4" Round Portable Aluminum Soccer Goals

SC1865PA40E Club 4" Round, 18 ½' x 6 ½' Aluminum Portable Goals

Face of goal shall be constructed of 4" round extruded 6063-T6 aluminum with a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have an 18 ½' wide x 6 ½' high opening.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 6 ½' bottom depth.

4" round face of the goal shall have a white textured polyester powder coated finish. Goal shall comply with ASTM F2056 and shall carry an 8-year limited warranty.

Standard features shall include auger type rear safety hold downs, molded plastic net attachment clips, rear horizontal stabilizer bars, Velcro net straps and net ground stakes. System shall weigh approximately 345#/pair.

SC1865PA40NT No Tip™ Club 4" Round, 18 ½' x 6 ½' Aluminum Portable Goals

Face of goal shall be constructed of 4" round extruded 6063-T6 aluminum with a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 6 ½' bottom depth.

4" round face of the goal shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty.

Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels.

Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. System shall weigh approximately 450#/pair

SC1865PA40NT No Tip™ Club 4" Round, 18 ½' x 6 ½' Aluminum Portable Goals

Face of goal shall be constructed of 4" round extruded 6063-T6 aluminum with a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 6 ½' bottom depth.

4" round face of the goal shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty.

Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels.

Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. System shall weigh approximately 450#/pair.

SC2170PA40E Club Plus 4" Round, Official 21' x 7' Aluminum Portable Goals

Face of goal shall be constructed of 4" round extruded 6063-T6 aluminum with a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 21' wide x 7' high opening.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 7' bottom depth.

4" round face of the goal shall have a white textured polyester powder coated finish. Goal shall comply with ASTM F2056 and shall carry an 8-year limited warranty.

Standard features shall include auger type rear safety hold downs, molded plastic net attachment clips, rear horizontal stabilizer bars, Velcro net straps and net ground stakes. System shall weigh approximately 435#/pair.

SC2170PA40NT No Tip™ Club Plus 4" Round, 21' x 7' Aluminum Portable Goals

Face of goal shall be constructed of 4" round extruded 6063-T6 aluminum with a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 7' bottom depth.

4" round face of the goal shall have a white textured polyester powder coated finish. Goal shall carry an 8-year limited warranty.

Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels.

Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. System shall weigh approximately 490#/pair.

SC2480PA40E Competition 4" Round, Official 24' x 8' Aluminum Portable Goals

Face of goal shall be constructed of 4" round extruded 6063-T6 aluminum with a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

Goal shall be designed so that it can be assembled with an official 24' wide x 8' high opening (or 24' 1 1/4" or 24' 2" wide to compensate for the use of optional safety padding on the vertical posts without affecting the 24' goal width).

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 10' bottom depth.

4" round face of the goal shall have a white textured polyester powder coated finish. Goal shall meet all NCAA, NF and FIFA rules and comply with ASTM F2056 and shall carry an 8-year limited warranty.

Standard features shall include auger type rear safety hold downs, molded plastic net attachment clips, rear horizontal stabilizer bars, Velcro net straps and net ground stakes. System shall weigh approximately 435#/pair.

SC2480PA40NT No Tip™ Competition 4' Round, Official 24' x 8' Aluminum Portable Goals

Face of goal shall be constructed of 4" round extruded 6063-T6 aluminum with a minimum wall thickness of .08". Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system.

Goal shall be designed so that it can be assembled with an official 24' wide x 8' high opening (or 24' 1 1/4" or 24' 2" wide to compensate for the use of optional safety padding on the vertical posts without affecting the 24' goal width).

The backstays and rear stabilizer bar shall be constructed of 1 5/8" diameter x 13 ga. minimum galvanized steel tube and provide a 4' top depth x 10' bottom depth.

4" round face of the goal shall have a white textured polyester powder coated finish. Goal shall meet all NCAA, NF and FIFA rules and comply with ASTM F2056 and shall carry an 8-year limited warranty.

Each goal shall include two 11" diameter by 12" wide molded polyethylene ballast drums that act as rear ballast to comply with ASTM F2056 when filled with sand at time of installation. Rear drums shall rotate on a tubular rear horizontal stabilizer bar and serve as transport wheels.

Additional standard features shall include molded plastic net attachment clips, 4mm white nets, Velcro net straps and net ground stakes. System shall weigh approximately 540#/pair.