

4" Square In-Ground Aluminum Soccer Goals

SC44S Ground Sleeve for Bison Permanent/Semi-Permanent Soccer Goals

Sleeves shall be constructed of 6063-T6 extruded aluminum and require bury in an 8" x 30" minimum footing. Actual sleeve depth shall be 24" and be designed to allow removal of 4" square uprights on Bison in-ground soccer goals. Sleeve shall have a removable steel top cap and shall weigh approximately 5#/each.

SC02BS European Style Backstays

Backstays shall be constructed of 1 5/8" diameter, 13 ga. minimum steel tubing formed to provide a 4' goal top depth. Design shall allow retrofitting to all Bison 4" square aluminum in-ground soccer goals. Backstays shall be finished with a white polyester powder coated finish and weigh 20#/pair.

SC0945IGA Bantam 4" x 4", 9' x 4 1/2' Aluminum Permanent/Semi Permanent Soccer Goals

Face of goal shall be constructed of 4" square aluminum extrusions with a minimum 3/4" corner radii for safety and a minimum .08" ga. wall thickness. Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 9' wide and 4 1/2' high opening.

Design shall allow for 24" of upright to be permanently buried in a 30" deep footing or installed in optional SC44S ground sleeves.

All components shall be finished with a textured white polyester powder coated finish. Goals shall carry a 5-year limited warranty. Nets and optional European backstays shall be ordered separately. System shall weigh approximately 185#/pair.

SC1265IGA Youth 4" x 4" 12' x 6.5' Aluminum Permanent/Semi Permanent Soccer Goals

Face of goal shall be constructed of 4" square aluminum extrusions with a minimum 3/4" corner radii for safety and a minimum .08" ga. wall thickness. Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 12' wide and 6 1/2' high opening.

Design shall allow for 24" of upright to be permanently buried in a 30" deep footing or installed in optional SC44S ground sleeves.

All components shall be finished with a textured white polyester powder coated finish. Goals shall carry a 5-year limited warranty. Nets and optional European backstays shall be ordered separately. System shall weigh approximately 215#/pair.

SC1865IGA Club 4" x 4", 18 ½' x 6 ½' Aluminum Permanent/Semi Permanent Soccer Goals

Face of goal shall be constructed of 4" square aluminum extrusions with a minimum ¾" corner radii for safety and a minimum .08" ga. wall thickness. Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have an 18 ½' wide and 6 ½' high opening.

Design shall allow for 24" of upright to be permanently buried in a 30" deep footing or installed in optional SC44S ground sleeves.

All components shall be finished with a textured white polyester powder coated finish. Goals shall carry a 5-year limited warranty. Nets and optional European backstays shall be ordered separately. System shall weigh approximately 235#/pair.

SC2170IGA Club Plus 4" x 4", 21' x 7' Aluminum Permanent/Semi-Permanent Soccer Goals

Face of goal shall be constructed of 4" square aluminum extrusions with a minimum ¾" corner radii for safety and a minimum .08" ga. wall thickness. Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 21' wide and 7' high opening.

Design shall allow for 24" of upright to be permanently buried in a 30" deep footing or installed in optional SC44S ground sleeves.

All components shall be finished with a textured white polyester powder coated finish. Goals shall carry a 5-year limited warranty. Nets and optional European backstays shall be ordered separately. System shall weigh approximately 265#/pair.

SC2480IGA Competition 4" x 4", 24' x 8' Aluminum Permanent/Semi-Permanent Soccer Goals

Face of goal shall be constructed of 4" square aluminum extrusions with a minimum ¾" corner radii for safety and a minimum .08" ga. wall thickness. Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 24' wide and 8' high opening.

Design shall allow for 24" of upright to be permanently buried in a 30" deep footing or installed in optional SC44S ground sleeves.

All components shall be finished with a textured white polyester powder coated finish. Goals shall meet all NCAA, NF and FIFA rules and carry a 5-year limited warranty. Nets and optional European backstay shall be ordered separately. System shall weigh approximately 275#/pair.

SC2480IGAFB Combination Soccer/Football Aluminum Permanent/Semi-Permanent Goals

Face of soccer goal shall be constructed of 4" square aluminum extrusions with a minimum $\frac{3}{4}$ " corner radii for safety and a minimum .08" ga. wall thickness. Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. Goal shall have a 24' wide and 8' high opening.

2 3/8" diameter aluminum football uprights shall extend 10' above the official 10' high horizontal football crossbar and be capable at being installed at either the official 23' 4" high school or 18' 6" college width.

Design shall allow for 24" of upright to be permanently buried in a 30" deep footing or installed in optional SC44S ground sleeves.

All components shall be finished with a textured white polyester powder coated finish. Goals shall carry a 5-year limited warranty. System shall weigh approximately 500#/pair.