

Face of goal shall be constructed of 4" square aluminum extrusions with a minimum 3/4" corner radii for safety and a minimum 1/8" wall thickness. 2 piece goal crossbar sections shall be connected by means of a telescoping inner aluminum extrusion using four hidden 3/8" x 1" hex bolts located on the rear of the crossbar. Extrusions shall have a net track extruded in the rear face to allow net attachment using specially designed clips included with each system. European style backstays and competition nets are included in goal. Goal shall have a 24' wide and 8' high opening. Design shall allow for 24" of upright to be permanently buried in a 30" deep footing or installed in optional SC44S ground sleeves. All components shall be finished with a textured white polyester powder coated finish. Goals shall meet all NCAA, NFHS and FIFA rules and carry a 5-year limited warranty. Goal shall be shipped in multiple pieces, and require onsite assembly. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings. System shall weigh approximately 460#/pair.

PRODUCT SPECIFICATION

SC2480IGA 4" SQUARE SHOOTOUT™ ALUMINUM PERMANENT/SEMI PERMANENT SOCCER GOALS

REVISED 6/30/22 L.M.

603 L Street, Lincoln, NE 68508 - Phone: (800) 247-7668 - Fax: (800) 638-0698 - www.ipibybison.com - sales@ipibybison.com